

IECEx Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Ex COMPONENT CERTIFICATE

Certificate No.:	IECEx BAS 16.0042U	Page 1	of 4	Certificate history:
Status:	Current	Issue N	o: 4	Issue 3 (2021-05-11) Issue 2 (2020-12-22)
Date of Issue:	2021-07-12			Issue 1 (2019-01-16) Issue 0 (2016-03-10)
Applicant:	nVent Thermal LLC 307 Constitution Drive Menlo Park CA 94025 United States of America			
Ex Component:	C25-100-Metal / C3/4-100-Metal Connection K	it		
	OT intended to be used alone and requires addit tmospheres (refer to IEC 60079-0).	ional consideration when in	corporated into other eq	uipment or systems
Type of Protection:	Increased Safety, Dust Protected			
Marking:	Ex eb IIC Gb or Ex db IIC Gb Ex tb III C Db			
Approved for issue or Certification Body:	n behalf of the IECEx	R S Sinclair		
Position:		Technical Manager	RSSel	~
Signature: (for printed version)				
Date:			12/7/2021	
2. This certificate is not	chedule may only be reproduced in full. transferable and remains the property of the issuing body enticity of this certificate may be verified by visiting www.ie	cex.com or use of this QR Code.		
Certificate issued			-	
SGS Baseefa Lin Rockhead Busin Staden Lane Buxton, Derbysh United Kingdom	ess Park nire, SK17 9RZ		S	GS



IECEx Certificate of Conformity

TM						
Certificate No.:	IECEx BAS 16.0042U		Page 2 of 4			
Date of issue:	2021-07-12		Issue No: 4			
Manufacturer:	nVent Thermal LLC 307 Constitution Drive Menlo Park CA 94025 United States of Amer	ica				
Additional manufacturing locations:	Parque Industrial del No	Plant 5 Facility Av. Industrial Falcon Lotes, 6 al 8 S/N Parque Industrial del Norte Reynosa Tampaulipas 88736				
This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended						
STANDARDS : The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards						
IEC 60079-0:2017 Explosive atmospheres - Part 0: Equipment - General requirements Edition:7.0						
IEC 60079-1:2014-06 Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d" Edition:7.0						
IEC 60079-31:2013 Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t" Edition:2						
IEC 60079-7:2017 Edition:5.1						
This Certificate does not indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.						
TEST & ASSESSMENT REPORTS: A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:						
Test Reports:						
GB/BAS/ExTR16.000 GB/BAS/ExTR21.000		GB/BAS/ExTR18.0101/00	GB/BAS/ExTR20.0176/00			
Quality Assessment Reports:						
GB/BAS/QAR06.003	BAS/QAR06.0030/09 GB/SIR/QAR09.0018/14					



Date of issue:

IECEx Certificate of Conformity

Certificate No.: IECEx BAS 16.0042U

Page 3 of 4

2021-07-12

Issue No: 4

Ex Component(s) covered by this certificate is described below:

The C25-100-Metal / C3/4-100-Metal connection kit is for use with parallel trace heating systems to provide an appropriate connection and insulation for trace heating cable into an Ex certified enclosure. It comprises a C1 Core Sealer to IECEx BAS 15.0137U and a cable gland to IECEx SIR 05.0020X. The cable gland is either brass or stainless steel. The connection kit comes in two forms:

The C25-100-Metal connection kit utilizes a M25 cable gland.

The C3/4-100-Metal connection kit utilizes a ³/₄ inch NPT cable gland.

Both variants can be Nickel Plated and are designated with a -NP suffix.

The kit contains:

- 1 gland
- 1 grommet
- 1 locknut
- 1 washer
- 1 insulation sleeve (green/yellow) for insulating the braid/ground wire.

SCHEDULE OF LIMITATIONS:

- 1. The service temperature range for the C25-100-Metal / C3/4-100-Metal Connection Kit is -60°C to +180°C.
- 2. When the C25-100-Metal / C3/4-100-Metal Connection Kit is used, it shall be mounted to an enclosure in accordance with the manufacturer's instructions.

3. The installer is to carry out a dielectric strength test on the Ex equipment in which the C25-100-Metal / C3/4-100-Metal Connection Kit is fitted. No dielectric breakdown shall occur. (Alternatively, an insulation resistance test may be undertaken in accordance with IEC 60079-30-2).

4. The integral C1 Core Sealer shall be installed inside an Ex equipment certified enclosure.



IECEx Certificate of Conformity

Certificate	No.:	IEC
Certificate	No.:	IEC

IECEx BAS 16.0042U 2021-07-12 Page 4 of 4

Issue No: 4

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above)

Variation 4.1

Date of issue:

To allow the C25-100-METAL / C3/4-100-METAL Connection Kit to be used with HTV heating cable.

Variation 4.2

To allow the C25-100-METAL / C3/4-100-METAL Connection Kit to be alternatively marked 'Ex db IIC Gb'.

	ExTR: GB/BAS/ExTR21.0060/00	File Reference: 21/0234
--	-----------------------------	-------------------------