

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-2229475-0
Report Reference EX26895-20220630
Date 11-Jul-2022

Issued to: ERICO INTERNATIONAL CORPORATION
34600 SOLON RD
SOLON, OH 44139-2631
United States

**This is to certify that
representative samples of**

VGMI - Sway-brace Devices, Nonrigid Type for Sprinkler
Systems

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 203A | Edition: 1 | Issue Date: 2015-12-18 | Revision
Date: 2019-8-8

Additional Information: See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-2229475-0
Report Reference EX26895-20220630
Date 11-Jul-2022

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
CSB12CBL	Cable and cable fittings
CSB18CBL	Cable and cable fittings
CSB2W(Y Y)URC(W W)L(Z Z), WW = Fastener Size 14=1/4 38= 3/8 12= 1/2 58= 5/8 34= 3/4 78= 7/8 Y Y = Cable Size 12= 3/32 18= 1/8 36= 3/16 Z Z = Cable Length in increments of feet.	Fittings
CSB36CBL	Cable and cable fittings
CSBBARJ(XX) + CSBURC12, (XX) indicates the coating finish designation- EG = Electrogalvanized, HD = Hot-Dipped, PL = Plain	Structure attachment fittings and adapters
CSBBC075(XX) + CSBNPC12, (XX) indicates the coating finish designation- EG = Electrogalvanized, HD = Hot-Dipped, PL = Plain	Structure attachment fittings and adapters
CSBBC075(XX) + CSBURC12, (XX) indicates the coating finish designation- EG = Electrogalvanized, HD = Hot-Dipped, PL = Plain	Structure attachment fittings and adapters
CSBIB075085(XX) + CSBNPC12, (XX) indicates the coating finish designation- EG = Electrogalvanized, HD = Hot-Dipped, PL = Plain	Structure attachment fittings and adapters
CSBIB075085(XX) + CSBURC12, (XX) indicates the coating finish designation- EG = Electrogalvanized, HD = Hot-Dipped, PL = Plain	Structure attachment fittings and adapters
CSBIB075145(XX) + CSBNPC12, (XX) indicates the coating finish designation- EG = Electrogalvanized, HD = Hot-Dipped, PL = Plain	Structure attachment fittings and adapters
CSBIB075145(XX) + CSBURC12, (XX) indicates the coating finish designation- EG = Electrogalvanized, HD = Hot-Dipped, PL = Plain	Structure attachment fittings and adapters
CSBIB125180(XX) + CSBNPC12, (XX) indicates the coating finish designation- EG = Electrogalvanized, HD = Hot-Dipped, PL = Plain	Structure attachment fittings and adapters
CSBIB125180(XX) + CSBURC12, (XX) indicates the coating finish designation- EG = Electrogalvanized, HD = Hot-Dipped, PL = Plain	Structure attachment fittings and adapters



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-2229475-0
Report Reference EX26895-20220630
Date 11-Jul-2022

CSBMA050050(XX) + CSBNPC12, (XX) indicates the coating finish designation- EG = Electrogalvanized, HD = Hot-Dipped, PL = Plain	Structure attachment fittings and adapters
CSBMA050050(XX) + CSBURC12, (XX) indicates the coating finish designation- EG = Electrogalvanized, HD = Hot-Dipped, PL = Plain	Structure attachment fittings and adapters
CSBMA050075(XX) + CSBNPC12, (XX) indicates the coating finish designation- EG = Electrogalvanized, HD = Hot-Dipped, PL = Plain	Structure attachment fittings and adapters
CSBMA050075(XX) + CSBURC12, (XX) indicates the coating finish designation- EG = Electrogalvanized, HD = Hot-Dipped, PL = Plain	Structure attachment fittings and adapters
CSBNPC(WW)	Fittings
CSBS1 + CSBURC12	Structure attachment fittings and adapters
CSBS2 + CSBURC12	Structure attachment fittings and adapters
CSBS3 + CSBURC12	Structure attachment fittings and adapters
CSBS4 + CSBURC12	Structure attachment fittings and adapters
CSBS5 + CSBURC12	Structure attachment fittings and adapters
CSBURC(WW), WW = Fastener Size 14=1/4 38= 3/8 12= 1/2 58= 5/8 34= 3/4 78= 7/8 YY = Cable Size 12= 3/32 18= 1/8 36= 3/16 ZZ = Cable Length in increments of feet.	Fittings
CSBURCR(WW), WW = Fastener Size 14=1/4 38= 3/8 12= 1/2 58= 5/8 34= 3/4 78= 7/8 YY = Cable Size 12= 3/32 18= 1/8 36= 3/16 ZZ = Cable Length in increments of feet.	Fittings

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

